Light reflectance value.

Highline 750

page 2 – 3

Reform Maze

page 4 - 6

ege testcertificate

| Subject: | Light Reflectance | | |
|------------------------|---|--|--|
| | | | |
| Reference No.: | 1316 | | |
| | | | |
| Reference: | Highline 750 | | |
| | | | |
| Description of sample: | Tuftet carpet, cut pile | | |
| | Colour palettes | | |
| | 5500 Colour Scale 1-12 | | |
| | 5520 Colour Scale 1-12 | | |
| | 5575 Colour Scale 1-12 | | |
| | 5595 Colour Scale 1-12 | | |
| Testing atmosphere | Unless otherwise specified the sample has been conditioned and tested, where appropiate, in the standard atmosphere for conditioning and testing textiles EN ISO 139:2005 of $65 \pm 4 \%$ R.H. and 20 $\pm 2 \degree$ C. | | |

Background

LRV is an instrumental measurement made using a spectrophotometer.

It is equivalent to CIE Y and is the proportion of visible light reflected by a surface, weighted for the sensitivity to light of the human eye.

LRV is expressed on a scale of 0-100 where absolute white has a value of 100 and absolute black has a value of 0. In practice white may be about 85 and black about 6.

For people with adequate vision, difference in hue or chroma (colour intensity), provide sufficient visual contrast. But for people who are visually impaired the main feature of a surface which determines the ability to identify differences in colour is the amount of light the surface reflects, or it's LRV.

Test procedure

The light reflectance value for the sample was determined using a Chroma Meter reflectance spectrophotometer with a large area CR-410 measuring head.

The sample was subjected to measurements and viewed at 0° with illuminant C. The light reflectance was determined using CIE Y, according to BS 8493:2008.



egetæpper a/s Industrivej Nord 25 Postbox 190 DK-7400 Herning

Tel: +45 97 11 88 11 Fax: +45 97 11 95 80

ege@ege.dk www.egecarpet.com

CVR 38 45 42 18

| Colour no. | Colour palette 5500 | Colour no. | Colour palette 5520 | Colour no. | Colour palette 5575 | Colour no. | Colour palette 5595 |
|------------------|---------------------------|------------------|---------------------------|------------------|---------------------------|------------------|---------------------------|
| gb1 – K40501 | 13,41 | gb1 - A20041 | 56,43 | gb1 - K28328 | 40,83 | gb1 - K28601 | 24,86 |
| gb2 – K40502 | 2,28 | gb2 - A20042 | 30,13 | gb2 - K28329 | 25,38 | gb2 - K28602 | 12,77 |
| gb3 – K40503 | 9,95 | gb3 - A20043 | 13,73 | gb3 - K28378 | 15,24 | gb3 - K28603 | 5,34 |
| gb4 – K40504 | 38,50 | gb4 - K20044 | 8.05 | gb4 - K28374 | 5,77 | gb4 - K20012 | 2,20 |
| gb5 – K40505 | 3,09 | gb5 - K20045 | 4,00 | gb5 - K28366 | 2,87 | gb5 - H28605 | 2,30 |
| gb6 – K40506 | 3,58 | gb6 - K20046 | 10,04 | gb6 - K28364 | 4,94 | gb6 - K28606 | 3,60 |
| gb7 – K40507 | 2,99 | gb7 - K20047 | 4,34 | gb7 - K28380 | 16,80 | gb7 - K28607 | 3,88 |
| gb8 – K40508 | 10,00 | gb8 - K20048 | 15,52 | gb8 - K28379 | 22,79 | gb8 - K28608 | 12,07 |
| gb9 - K40509 | 4,48 | gb9 - K20049 | 5,10 | gb9 - K27886 | 17,31 | gb9 - K28609 | 18,06 |
| gb10 – K40510 | 12,05 | gb10 - K20050 | 5,42 | gb10 - K28360 | 18,23 | gb10 - K28610 | 7,76 |
| gb11 – K40511 | 4,60 | gb11 - K20051 | 2,97 | gb11 - K28367 | 6,42 | gb11 - H28611 | 3,38 |
| gb12 – K40512 | 16,06 | gb12 - K20012 | 2,19 | gb12 - K28368 | 2,67 | gb12 - H28632 | 2,71 |

Test results CIE Y :

The information contained on page no 1-2 of this certificate is hereby certified to be correct statement of the tests and investigations carried out by ege testlaboratory on the material reffered to.

Signed by

Dorthe Dav Pedesen

Dorthe Daa Pedersen Laboratory Technician

Reported By

Hychm.

Henrik Schmidt Hansen Group CSR Director

Herning 06.10.2022



ege testcertificate

| Subject: | Light Reflectance |
|------------------------|---|
| Reference No.: | 1959 |
| Reference: | Reform Maze |
| Description of sample: | Standard colors |
| Testing atmosphere | Unless otherwise specified the sample has been conditioned and tested, where appropiate, in the standard atmosphere for conditioning and testing textiles EN ISO 139:2005 of 65 \pm 4 % R.H. and 20 \pm 2 °C. |

Background

LRV is an instrumental measurement made using a spectrophotometer.

It is equivalent to CIE Y and is the proportion of visible light reflected by a surface, weighted for the sensitivity to light of the human eye.

LRV is expressed on a scale of 0-100 where absolute white has a value of 100 and absolute black has a value of 0. In practice white may be about 85 and black about 6.

For people with adequate vision, difference in hue or chroma (colour intensity), provide sufficient visual contrast. But for people who are visually impaired the main feature of a surface which determines the ability to identify differences in colour is the amount of light the surface reflects, or it's LRV.

Test procedure

The light reflectance value for the sample was determined using a Chroma Meter reflectance spectrophotometer with a large area CR-410 measuring head.

The sample was subjected to measurements and viewed at 0° with illuminant C. The light reflectance was determined using CIE Y, according to BS 8493:2008.



Test results CIE Y :

Reform Maze Broadloom

| Color ref | Result | Color ref | Result |
|-----------|--------|-----------|--------|
| 0922150 | 7,54 | 0922650 | 15,83 |
| 0922170 | 5,67 | 0922710 | 22,94 |
| 0922220 | 26,22 | 0922720 | 21,75 |
| 0922240 | 14,33 | 0922725 | 17,50 |
| 0922320 | 9,64 | 0922730 | 14,92 |
| 0922350 | 5,42 | 0922735 | 16,21 |
| 0922420 | 9,58 | 0922740 | 15,36 |
| 0922450 | 5,78 | 0922745 | 12,61 |
| 0922510 | 21,76 | 0922750 | 11,70 |
| 0922520 | 7,06 | 0922760 | 6,62 |
| 0922530 | 13,65 | 0922780 | 6,60 |
| 0922540 | 11,32 | 0922850 | 6,71 |
| 0922550 | 6,27 | 0922870 | 6,00 |
| 0922580 | 3,87 | | |

Reform Maze Tiles

| Color ref | Result | Color ref | Result |
|-----------|--------|-----------|--------|
| 092215048 | 7,54 | 092265048 | 15,83 |
| 092217048 | 5,67 | 092271048 | 22,94 |
| 092222048 | 26,22 | 092272048 | 21,75 |
| 092224048 | 14,33 | 092272548 | 17,50 |
| 092232048 | 9,64 | 092273048 | 14,92 |
| 092235048 | 5,42 | 092273548 | 16,21 |
| 092242048 | 9,58 | 092274048 | 15,36 |
| 092245048 | 5,78 | 092274548 | 12,61 |
| 092251048 | 21,76 | 092275048 | 11,70 |
| 092252048 | 7,06 | 092276048 | 6,62 |
| 092253048 | 13,65 | 092278048 | 6,60 |
| 092254048 | 11,32 | 092285048 | 6,71 |
| 092255048 | 6,27 | 092287048 | 6,00 |
| 092258048 | 3,87 | | |

The information contained on page no 1 & 2 of this certificate is hereby certified to be correct statement of the tests and investigations carried out by ege test laboratory on the material refered to.

Signed by

Reported By



Dorthe Daa Pedersen

Dorthe Dad Pederson

Laboratory Technician

un

Henrik Schmidt Hansen QUALITY & ENVIRONMENTAL DIRECTOR

