



**TEXTILNÍ ZKUŠEBNÍ ÚSTAV, s.p.**  
(TEXTILE TESTING INSTITUTE)

**Notified body No. 1021**

Cejl 480/12, Zábřdovice, 602 00 Brno, Czech Republic

issues



## CERTIFICATE OF CONSTANCY OF PERFORMANCE

**No. 1021 - CPR – 006-2/16**

In compliance with Regulation No. 305/2011 (EU) of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products (Construction Products Regulation – CPR), in valid wording, Annex V, art. 1.2 b)

### Textile floor coverings: Product group 1C - PA-WT

Material:	100% polyamide
Primary backing:	polypropylene or polyester
Secondary backing:	woven secondary backing (polypropylene)
Technology:	tufted – cut pile/ tufted – loop pile/ woven – loop pile

Products placed on the market under the name or trade mark of:

Manufacturer: **Ege Carpets A/S**  
Industrivej Nord 25, DK-7400 Herning, Denmark  
ID: CVR 38454218

Manufacture location: 1) Ege Carpets A/S - Industrivej Nord 25, DK-7400 Herning, Denmark  
2) Ege Carpets A/S - Industrivej 3, DK-6510 Gram, Denmark

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard:

**EN 14041:2004/ AC:2006 Resilient, textile and laminate floor coverings – Essential characteristics**

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

Products fulfil the essential characteristic of reaction to fire: **Class C<sub>fl</sub> – s1**

The present certificate was issued on the basis of the protocol No. 1021/16/033 (22.02.2016), No. 1021/16/187 (15.08.2016), No. 1021/17/006 (11.01.2017), No. 1021/16/033/K1 (03.03.2017), No. 1021/17/267 (04.10.2017), No. 1021/18/071 (13.04.2018), No. 1021/18/183 (12.07.2018), No. 1021/20/115 (16.04.2020) and No. 1021/20/330 from 22.09.2020 issued by NB 1021 TZÚ Brno. Detailed description of product group is stated in Annex No. 1 of the certificate.

This certificate was first issued on February 22, 2016 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.



Brno, 22.09.2020



RNDr. Pavel Malčík  
Managing Director

**TEST REPORTS and DOCUMENTATION:**

<i>Product</i>	<i>Test report</i>	<i>Date</i>	<i>Accredited laboratory</i>	<i>Product documentation</i>
<b>Epoca Texture WT</b>	PF13282d	9.12.2010	DBI	3. – 4. 2.2016
<b>Epoca Texture 2000 WT</b>	VN710 126628.1	8.2.2017	OETI	
<b>Epoca Twist WT</b>				
<b>Highline 1100 WT</b>	PF12442d	12.10.2006	DBI	
<b>Highline 750 WT</b>	PF13187	5.11.2009	DBI	
<b>Highline 910 WT</b>				
<b>Epoca Silky WT</b>	PF12442hh	9/2006	DBI	3.10.2017
<b>Ege Tuft 440 WT</b>	PFA10531	31.3.2014	DBI	18.2.2016
<b>Highline Carré WT</b>				3. – 4. 2.2016
<b>Ege Tuft 950 WT</b>	PFA10683	9.2.2015	DBI	
<b>Epoca Chess WT</b>	PF12442w	9.11.2006	DBI	
<b>Epoca Classic WT</b>	PF12442q	15.10.2006	DBI	
<b>Epoca Classic 1/10 WT</b>				
<b>Epoca Ribs WT</b>	PF12442r	8.11.2006	DBI	
<b>Highline Loop WT</b>				
<b>ReForm Calico WT</b>				
<b>Una Tempo WT</b>				
<b>Highline Loop e16 WT</b>				
<b>Epoca Compact WT</b>	VNLF 082004.1	25.1.2016	OETI	
<b>Epoca Globe WT</b>	PF12369		DBI	
<b>Epoca Knit WT</b>	PFA10642	11.11.2014	DBI	
<b>Epoca Plait WT</b>				
<b>Epoca Pro WT</b>				
<b>Epoca Profile WT</b>	PFA10468b	9.1.2014	DBI	
<b>Epoca Rasp WT</b>				
<b>Epoca Structure WT</b>	VNLF 082004.1	25.1.2016	OETI	
<b>Una Casa WT</b>	PFA10675		DBI	
<b>Una Micro WT</b>	PFA10625b	11.11.2014	DBI	
<b>Rawline WT</b>	VNLF 083456.2	24.6.2016	OETI	
<b>Epoca Frame WT</b>				12.07.2018
<b>Contra 2018 WT</b>	VN710140525.1	12.6.2018	OETI	
<b>Epoca Moss WT</b>	VN710140527.1	12.5.2018	OETI	31.3.2020
<b>Una Brick WT</b>	VN710165498.1	16.3.2020	OETI	



**SCOPE:**

**Group 1C - PA-WT (100% Polyamide / Woven secondary backing)**

<b>Group 1.1 (PA-WT)</b>		Tufted	Cut Pile
<b>Class C<sub>n</sub> - s1</b>			
<i>Total weight</i>	2 150 – 3 550 g.m <sup>-2</sup>	<i>Total thickness</i>	7 – 15,5 mm
<i>Pile weight</i>	750 – 2 000 g.m <sup>-2</sup>	<i>Pile thickness</i>	5 – 13 mm
<i>Classification report</i>	VN710 174089.1-2 (21.9.2020)	<i>Classification</i>	EN 13501-1 + A1
<i>Products in group</i>	<b>Epoca Texture WT</b>	<b>Highline 750 WT</b>	<b>Highline 1100 WT</b>
	<b>Epoca Twist WT</b>	<b>Highline 910 WT</b>	<b>Epoca Silky WT</b>
	<b>Epoca Texture 2000 WT</b>	<b>Contract 2018 WT</b>	<b>Epoca Moss WT</b>

<b>Group 1.2 (PA-WT)</b>		Tufted	Loop Pile
<b>Class C<sub>n</sub> - s1</b>			
<i>Total weight</i>	2 050 – 2 750 g.m <sup>-2</sup>	<i>Total thickness</i>	5 – 8 mm
<i>Pile weight</i>	440 – 1 100 g.m <sup>-2</sup>	<i>Pile thickness</i>	3 – 4 mm
<i>Classification report</i>	VN710 174089.1-2 (21.9.2020)	<i>Classification</i>	EN 13501-1 + A1
<i>Products in group</i>	<b>Ege Tuft 440 WT</b>	<b>Epoca Classic WT</b>	<b>ReForm Calico WT</b>
	<b>Ege Tuft 950 WT</b>	<b>Epoca Classic 1/10 WT</b>	<b>Highline Loop WT</b>
	<b>Highline Loop e16 WT</b>	<b>Epoca Ribs WT</b>	<b>Una Tempo WT</b>
	<b>Epoca Frame WT</b>	<b>Epoca Chess WT</b>	<b>Highline Carré WT</b>

<b>Group 1.3 (PA-WT)</b>		Woven	Loop Pile
<b>Class C<sub>n</sub> - s1</b>			
<i>Total weight</i>	1 800 – 2 600 g.m <sup>-2</sup>	<i>Total thickness</i>	3 – 4,5 mm
<i>Pile weight</i>	345 – 700 g.m <sup>-2</sup>	<i>Pile thickness</i>	-
<i>Classification report</i>	VN710 174089.1-2 (21.9.2020)	<i>Classification</i>	EN 13501-1 + A1
<i>Samples in group</i>	<b>Epoca Compact WT</b>	<b>Epoca Plait WT</b>	<b>Epoca Rasp WT</b>
	<b>Epoca Globe WT</b>	<b>Epoca Pro WT</b>	<b>Epoca Structure WT</b>
	<b>Epoca Knit WT</b>	<b>Epoca Profile WT</b>	<b>Una Casa WT</b>
	<b>Una Micro WT</b>	<b>Rawline WT</b>	<b>Una Brick WT</b>

<b>Field of application</b>	Horizontal laid floor coverings in form of rolls. The carpet is to be mounted on a substrate of Euroclass A1 <sub>n</sub> or A2 <sub>n</sub> with a density of at least 1350 kg.m <sup>-3</sup> . It is declared for installation with a polyacrylat - copolymer dispersion adhesive (Ege 90RH/ UZIN UZ 57) or similar.
-----------------------------	---

