



TEXTILNÍ ZKUŠEBNÍ ÚSTAV, s.p.
(TEXTILE TESTING INSTITUTE)

Notified body No. 1021

Václavská 237/6, 603 00 Brno, Czech Republic

issues

CERTIFICATE OF CONSTANCY OF PERFORMANCE

No. 1021 - CPR – 006-2/16

In compliance with Regulation No. 305/2011 (EU) of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products (Construction Products Regulation – CPR), in valid wording, Annex V, art. 1.2 b)

Textile floor coverings: Product group 1C - PA-WT

Material:	100% polyamide
Primary backing:	polypropylene or polyester
Secondary backing:	woven secondary backing (polypropylene)
Technology:	tufted – cut pile/ tufted – loop pile/ woven – loop pile

Products placed on the market under the name or trade mark of:

Manufacturer: **Egetæpper A/S**
Industrivej Nord 25, DK-7400 Herning, Denmark
ID: CVR 38454218



Manufacture location: 1) Egetæpper A/S - Industrivej Nord 25, DK-7400 Herning, Denmark
2) Egetæpper A/S - Industrivej 3, DK-6510 Gram, Denmark

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard:

EN 14041:2004/ AC:2006 Resilient, textile and laminate floor coverings – Essential characteristics

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

Products fulfil the essential characteristic of reaction to fire: **Class C_{fl} – s1**

The present certificate was issued on the basis of the protocol No. 1021/16/033 (22.02.2016), No. 1021/16/187 (15.08.2016), No. 1021/17/006 (11.01.2017), No. 1021/16/033/K1 (03.03.2017), No. 1021/17/267 (04.10.2017), No. 1021/18/071 (13.04.2018) and No. 1021/18/183 from 12.07.2018 issued by NB 1021 TZU Brno. Detailed description of product group is stated in Annex No. 1 of the certificate.

This certificate was first issued on February 22, 2016 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.



Brno, 13.07.2018



RNDr. Pavel Malčík
Managing Director

TEST REPORTS and DOCUMENTATION:

<i>Product</i>	<i>Test report</i>	<i>Date</i>	<i>Accredited laboratory</i>	<i>Product documentation</i>
Epoca Texture WT	PF13282d	9.12.2010	DBI	3. – 4. 2.2016
Epoca Texture 2000 WT	VN710 126628.1	8.2.2017	OETI	
Epoca Twist WT				
Highline 1100 WT	PF12442d	12.10.2006	DBI	
Highline 750 WT	PF13187	5.11.2009	DBI	
Highline 910 WT				
Epoca Silky WT	PF12442hh	9/2006	DBI	3.10.2017
Ege Tuft 440 WT	PFA10531	31.3.2014	DBI	18.2.2016
Ege Tuft 950 WT	PFA10683	9.2.2015	DBI	
Epoca Chess WT	PF12442w	9.11.2006	DBI	3. – 4. 2.2016
Epoca Classic WT	PF12442q	15.10.2006	DBI	
Epoca Classic 1/10 WT				
Epoca Ribs WT	PF12442r	8.11.2006	DBI	
Highline Loop WT				
Una Tempo WT				
Highline Loop e16 WT				
Epoca Compact WT	VNLF 082004.1	25.1.2016	OETI	3. – 4. 2.2016
Epoca Globe WT	PF12369		DBI	
Epoca Knit WT	PFA10642	11.11.2014	DBI	
Epoca Plait WT				
Epoca Pro WT				
Epoca Profile WT	PFA10468b	9.1.2014	DBI	
Epoca Rasp WT				
Epoca Structure WT	VNLF 082004.1	25.1.2016	OETI	
Una Casa WT	PFA10675		DBI	
Una Micro WT	PFA10625b	11.11.2014	DBI	
Rawline WT	VNLF 083456.2	24.6.2016	OETI	
Epoca Frame WT				
Contra 2018 WT	VN710140525.1	12.6.2018	OETI	12.07.2018
Epoca Moss WT	VN710140527.1	12.5.2018	OETI	



SCOPE:

Group 1C - PA-WT (100% Polyamide / Woven secondary backing)

Group 1.1 (PA-WT)		Tufted	Cut Pile
Class C_n - s1			
<i>Total weight</i>	2 150 – 3 550 g.m ⁻²	<i>Total thickness</i>	7 – 15,5 mm
<i>Pile weight</i>	750 – 2 000 g.m ⁻²	<i>Pile thickness</i>	4,5 – 13 mm
<i>Classification report</i>	VN710 140527.2 (12.6.2018)	<i>Classification</i>	EN 13501-1 + A1
<i>Products in group</i>	Epoca Texture WT	Highline 750 WT	Highline 1100 WT
	Epoca Twist WT	Highline 910 WT	Epoca Silky WT
	Epoca Texture 2000 WT	Contra 2018 WT	Epoca Moss WT

Group 1.2 (PA-WT)		Tufted	Loop Pile
Class C_n - s1			
<i>Total weight</i>	2 050 – 2 750 g.m ⁻²	<i>Total thickness</i>	5 – 8 mm
<i>Pile weight</i>	440 – 1 100 g.m ⁻²	<i>Pile thickness</i>	3 – 4 mm
<i>Classification report</i>	VN710 140527.2 (12.6.2018)	<i>Classification</i>	EN 13501-1 + A1
<i>Products in group</i>	Ege Tuft 440 WT	Epoca Classic WT	Epoca Chess WT
	Ege Tuft 950 WT	Epoca Classic 1/10 WT	Highline Loop WT
	Highline Loop e16 WT	Epoca Ribs WT	Una Tempo WT
	Epoca Frame WT		

Group 1.3 (PA-WT)		Woven	Loop Pile
Class C_n - s1			
<i>Total weight</i>	1 800 – 2 600 g.m ⁻²	<i>Total thickness</i>	3 – 4,5 mm
<i>Pile weight</i>	345 – 700 g.m ⁻²	<i>Pile thickness</i>	-
<i>Classification report</i>	VN710 140527.2 (12.6.2018)	<i>Classification</i>	EN 13501-1 + A1
<i>Samples in group</i>	Epoca Compact WT	Epoca Plait WT	Epoca Rasp WT
	Epoca Globe WT	Epoca Pro WT	Epoca Structure WT
	Epoca Knit WT	Epoca Profile WT	Una Casa WT
	Una Micro WT	Rawline WT	

<i>Field of application</i>	Horizontal laid floor coverings in form of rolls. The carpet is to be mounted on a substrate of Euroclass A1 _n or A2 _n with a density of at least 1350 kg.m ⁻³ . It is declared for installation with a polyacrylat - copolymer dispersion adhesive (Ege 90RH/ UZIN UZ 57) or similar.
-----------------------------	---

